

SEALCON

800-456-9012 / 303-69<u>9-1135</u> www.sealconusa.com/ned

Two Outstanding Companies! One Dependable Source! Your Cable & Accessories Solution House!

We provide complete solutions for your application needs!









Renewable Energy



Food & Beverage



High Temperature



Robotics



Petro-Chemical \$25 Million Inventory!

Liquid Tight Strain Relief Fittings

Materials: Nylon, Nickel Plated Brass. Stainless Steel, PVDF & more! Threads: NPT, Metric, PG & BSPP, Cable Range: 0.08 - 3.54" (2 - 90 mm) Large Inventory, Great quality and affordable prices.



Accessories

Locking Nuts, O-Rings & Seal Rings, Inserts (Standard, Reduced & Multi-Hole) Dome & Hex Plugs, Cable Clamp. Socket & Ratchet Wrenches, Thread Adapters, Reducers and Enlargers, etc.



Circular Connectors

Sizes: M16, M23, M27, M40 **Signal:** 3 - 28 pins (8 - 20 Amps) Power: 6 & 8 pins (8 - 55 Amps) Types: Standard, Straight, Elbow, Panel, Push-Pull, Stainless Steel, Over-molded Solutions, RJ 45 Industrial Ethernet. Profinet. Applications: Robotic, Medical, Automation, Motion Technology, Packaging, Sensors,

EXIOS

Strain Relief Fittings, Cable Glands for Hazardous / Explosion Proof Areas

- Approvals: IECEx. ATEX. Ex-d / Ex-e / Ex-tD.
- Zone 1, Zone 2, Zone 20, Zone 21 and Zone 22
- Gas Groups IIA, IIB and IIC Apparatus Group III
- Equipment Protection Level GbDa
- · Interlocking Armor Cone
- Halogen- and phosphorous-free
- · Included: Silicone Seals and O-Rings
- Zero Torsion on cable core and armor, Dual seal
- Fast and easy assembly with maximum grip
- Temperature Range: -76°F to 221°F (-60°C to +105°C)
- IP 68 (5 bar), EN 60529
- Available Sizes:
- Metric: M16, M20, M25, M32, M40, M50, M63, M75
- NPT: 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"

Our Service makes the Difference!







Featured Products

Unsurpassed **Customer Service!**

One-Stop Shopping!

No Minimum Orders!

Samples Available!

Call for a Catalog!



For more information call us or visit our website!

31,000+ Items in Stocki Rubber / All-Weather Cable: H05 RN-F / H07 RN-F

- Hamonized / Oil Resistant
- Working Voltage: 750V
- Temperature Range: -22°F to 140°F (-30°C to +60°C)
- · Dry, Damp & Wet Areas, Outdoor applications
- · Typical Applications: Boilers, Heating Plates, Hand Lamps, Electric Tools, Lifts, Cranes, etc.



Hook-up Wire: FIVENORM

10-11

- · Approvals: HAR-UL-CSA-CE-AWM-MTW
- PVC Single Conductors, UL-Style 1015, 600V, 221°F (105°C)
- PVC self-extinguishing, Flame-retardant





AWM Style 1015 OR MTW ... AWG CSA - AWM I A/B 105°C 600

Camozzi Pneumatics

Cables & Wires

A one stop source for wires and cables requiring RoHS, UL, CSA, Harmonized

& CE approvals, Halogen-free, NCFR.

We offer cables for Power, Control,

High/Low Temp., Hi-Flex, Robotic, Track, Servo, VFD, Composite, Ribbon,

Data (CAT), Single Conductor, Etc!

Fittings: Brass & Composite Valves: Manual, Mechanical, Air-Pilot and Flow Control Valves

® ♥ ₩ ▲CE HAR MTW

Cylinders: Mini-Cylinders, Tie-Rod, Cylinders, Aluminum Profile Cylincers FRL Units: Filters, Regulators and Lubricators

The Cable, Wire & Enclosure Experts!



Conduit System

Fittings: Push-in, Turn-to-Seal. Double-Seal, Combination Conduit - Cable Strain Relief Fittings, Flange/Bulkhead

Corrugated Conduit: Standard & Superflex, Mounting Brackets



Solar Plus Enclosures (UV-protected)

Industrial Enclosures

Materials: Polycarbonate, ABS, EMI, Polyester, Polystyrene,

Aluminum, Powder-coated Steel, Stainless Steel Features: Square/rectangle shape, Solid & transparent lids, Smooth walls or

PG/Metric knockouts, Flanges, Extension Frames, Hinges & Latches. Applications: Indoor/Outdoor, Medical, Offshore, Marine, Wi-Fi, Hazardous Areas, Solar, etc. Accessories: Mounting Plates, DIN Rails, Lugs, Clips, Screws, etc.