



BSP/METRIC

4

FLOW CONTROL VALVES & ACCESSORIES

BSP/METRIC

Series 2901 - 2903 - 2921 Silencers

Series 2931 - 2938 - 2939 - 2905 - RSW

BSP-Metric

Ports M5 (10-32 UNF), G1/8, G1/4, G3/8, G1/2, G3/4, G1

The silencers are indispensable elements for eliminating or reducing the characteristic noise of compressed air during discharge operations. They should always be placed on the outlets of 3/2, 5/2 or 5/3-way valves.

When carrying out maintenance, the silencers should be degreased using mineral spirit or paraffin and compressed air blown through them in the opposite direction to operation.

This chapter is a general overview of the Flow Control Valve product line. For details of product data and dimensions, please see the *Fittings and Flow Control Valves Catalog*.



TECHNICAL SPECIFICATIONS

Construction	Body with male and female thread
Materials used for body	OT58 brass - copper (2921-2931) - polyethylene (2938)
Materials used for silencing	Stainless steel - bronze (sintered) - polyethylene
Ports	M5 (10-32 UNF), G1/8, G1/4, G3/8, G1/2, G3/4, G1
Noise threshold	See Fittings and Flow Control Valve Catalog for details

* The measurements were carried out at 6 bar



BSP/METRIC

Silencers Series 2901
Mod.

2901 1/8

2901 1/4-17

2901 1/4-22

2901 3/8

2901 1/2

2901 3/4

2901 1


Silencers Series 2903
Mod.

2903 1/8


Silencers Series 2931
Mod.

2931 M5

2931 M7

2931 1/8


2931 1/4

2931 3/8

2931 1/2

2931 3/4

2931 1


Silencers Series 2938
Mod.

2938 M5

2938 1/8

2938 1/4

2938 3/8

2938 1/2



Silencers Series 2939
Mod.

2939 4

2939 6

2939 8

2939 10


Flow controllers Mod. RSW...

Flow control valves with silencer.

Connections: G1/8, G1/4, G1/2

(for instructions, see p. 117 or p. 146)

Mod.

RSW 1/8

RSW 1/4

RSW 1/2


Flow controllers Series 2905

Silencer bushing for Mod. SCO... or MCO...

(for instructions, see p. 117 or p. 146)

Mod.

2905 1/8

2905 1/4

2905 3/8


4
FLOW CONTROL VALVES & ACCESSORIES
BSP/METRIC