

## PRODUCT LINE

Winding Wires  
Basic Insulation  
Supplemental Insulation  
Reinforced Insulation  
Lead Wires  
Hook Up Wires  
Coating of Fiber & Fiber Optic Cables  
Fillers  
Jacketing or Insulating on a Toll Basis  
Coax Cables  
Multi-Conductor Cables  
High Temperature Products  
Wire for Medical Application  
Wire Wrap in ETFE  
Underwater Products  
Thermocouple Wires  
**NEW** Self Bonding  
**NEW** 300°C  
Custom

## APPLICATIONS

Automotive  
Computers  
Electronics  
Medical Equipment/Devices  
Power Supplies  
Security Systems  
Telecommunications  
Transformers

## CONDUCTORS

- Size ranges from 4 AWG to 40 AWG
- Extensive range of conductors available
- Solid and stranded constructions
- Including Enamel and Litz Wire

## CERTIFICATIONS

UL, CSA, and VDE Approved

## INSULATING MATERIALS

Insulation thickness from .001" to .250"

ETFE	Polyethylene	Polyurethane
FEP	Foam Polyethylene	TPR
PFA	Polypropylene	TPE
PVC	Surlyn®	<b>NEW</b> ECA 3000
Medical PVC	Hytrel®	<b>NEW</b> Coilbond™

## POWER SUPPLY AND TRANSFORMER WIRE PRODUCTS

Solid, Stranded, Enamel, and Litz Wire conductors insulated with ETFE, FEP, or PFA

Insulation Systems available for Class B, Class F, and Class H Basic, Supplemental, and Reinforced Insulation per IEC & UL 60950-1  
IEC 61010, 61558 & 60601 Certified  
UL 60601

## UL AWM STYLES

1007, 1015, 1226, 1227, 1330, 1331, 1332, 1333, 1371, 1508, 1513, 1516, 1517, 1523, 1538, 1558, 1571, 1586, 1609, 1643, 1644, 1671, 1679, 1692, 1716, 1729, 1730, 1731, 1809, 1821, 1829, 1863, 1864, 1873, 1886, 1887, 1894, 1990, 10045, 10086, 10109, 10125, 10126, 10316

## MIL SPECS

Mil-W-81822/7, /8, /10, /12, /13

Mil-W-22759/16, /17, /18, /19

Mil-W-16878/1, /2, /3, /10, /11, /12, /13, /17, /18, /19, /33

*Custom wire and cable constructions are also available.*

*Please consult with your sales specialist*